



325 WATT - MODULE DATA SHEET			Module Design (Front)
ELECTRICAL PARAMETERS			
Model Name	ECO 325		
Cell Configurations (Nos.)	12 x 6 (72) Series		
Parameters	Value	Tolerance	
Pmax (W)	325	(0 to + 3.0%)	
Voc (V)	45.8	(± 3.0%)	
Isc (A)	9.13	(± 5.0%)	
Vmax (V)	37.6		
Imax (A)	8.65		
Fill Factor (%)	77.72%		
Module Efficiency (%)	16.77%		
Maximum System Voltage (VDC)	1000		
Temp. Coefficient of Pmax (%/°C)	-0.39		
Temp. Coefficient of Voc (%/°C)	-0.31		
Temp. Coefficient of Isc (%/°C)	0.06		
Electrical values measured at STC: 25 °C, 1.5AM, 1000 W/m ²			
MECHANICAL PARAMETERS			
Parameters	Measurement	Tolerance	
L - Length of Module (mm)	1960	± 1.0 mm.	
W - Width of Module (mm)	989	± 1.0 mm.	
H - Height of Module (mm)	40	± 0.5 mm.	
X - Pitch Distance (mm)	950	± 1.0 mm.	
Y- Pitch Distance (mm)	1200, 1600	± 1.0 mm.	
Mounting Hole (mm)	8 oblong of size 6.5 mm x 10 mm		
Grounding Hole (mm)	2 Nos. of Dia. 4mm on Length Side		
Cell	Polycrystalline Solar Cells, 156.75mmX156.75mm		
Junction Box	TUV approved, IP 65 / IP 67 rated 4 terminal junction box with 3 bypass diodes		
Cables	1000mm Long, 4mm ² cables with MC4 Compatible Connectors		
Weight	22 Kg.		

P V Power Technologies Pvt. Ltd.
 Plot – 60, Tarapur Textile Park Pvt. Ltd.
 (Sai Baba Boulevard Township),
 At – Gundale Village, Post – Mahagoan,
 Boisar (East), Dist/Tal – Palghar, Pin Code – 401501
 |www.pvpowertech.com|